

NCR SelfServ™ 34 WALK-UP

THROUGH-THE-WALL FULL-FUNCTION ATM

OFFER YOUR CUSTOMERS THE WIDEST RANGE OF TRANSACTIONS POSSIBLE

Designed to easily handle the highest of transaction volumes, the SelfServ 34 keeps serving your customers with a wide range of transactions like mixed cash and check deposit and bill payment. Created to cope with

the severest of weather conditions, the SelfServ 34 can be placed outdoors—helping you bring your brand closer to your customers.

Proactively fixes itself

Keep your ATMs up and running, offering your customers the transactions they want, when and where they need them. NCR's express recovery and self-healing technologies reduce downtime from hours to minutes—making your ATMs available around the clock.

Keeps you informed

Successful network management is about having the right information at your fingertips. NCR SelfServ ATMs provide data in real-time on configurations, software versions and the activity levels of each module. So you can see, understand and control your entire network—and make more empowered decisions.

Inspire trust in your ATM network

Our SelfServ ATMs are designed to defend against known and unknown fraud attacks, even before they start. Ask us about our multi-layered approach to ATM security including logical and physical solutions. For example, Solidcore Suite for APTRA™ protects against the execution of unauthorized code on your ATM network and our Skimming Protection Solution protects cardholder data from card skimming attacks.



For more information, visit ncr.com, or email ncr.financial@ncr.com.



TECHNICAL SPECIFICATIONS

PRODUCT DIMENSIONS

- HEIGHT 59.0" (1,498mm)
- WIDTH 30.4" (773mm)
- DEPTH
 - Standard sleeve 51.2" (1,300mm)
 - Short sleeve 46.7" (1,187mm)
- WEIGHT
 - CEN I safe 1.936lbs (878kg)
 - CEN III/IV safe 2.284lbs (1,036kg)

CUSTOMER INTERFACE

- Display - 15" LCD, FDK or touchscreen, optional privacy filter, sunlight readable displays
- Keyboard - EPP (PCI compliant), polycarbonate or stainless steel. Optional Alphanumeric keyboard
- Card Reader - Smart Dip, IMCRW with Smart option, HiCo
- Integrated Media Entry and Exit Indicators (MEEI)
- Audio - Optional high quality public audio and/or sound jack with volume control
- Advert Panel - Standard or enhanced with backlight
- Barcode Reader - 2D Barcode supports both 1D and 2D documents 1D and 2D documents

DISPENSER

- S2 Media Dispense Module, 2-4 cassettes, bunch presenter
- Dual Dispense 2 x 4 (8 cassettes)
- Configurable purge bin capability with retract and single note divert
- Anti-overfill cassette

SERVICING

- LCD Operator Panel (rear load only)
- Front, rear and side service

PRINTERS

- Receipt Printer - 80mm 203dpi graphics thermal printer. Options - retract and capture, dual roll and/or 2ST™ (two-sided thermal printing)
- Journal Printer - 80mm 203dpi graphics thermal printer (E-Journal available as default)
- Full page thermal printer with document capture and 2ST
- Passbook Printer - Page-turning passbook for horizontally stitched books

SECURITY

- NCR Secure™ is a complete portfolio of multi-layered solutions and services designed to provide protection against ATM attacks. Including a range of physical enclosures, recessed PIN Pad and Solidcore software security to protect your network

DEPOSIT TECHNOLOGY

- Intelligent Cash Deposit and Recycling Options - Choice of Cash Acceptors and Recycler. Accepts and validates up to 200 new notes per transaction*
- Supports multi-currency deposit, remote download of templates
- Intelligent Check Deposit - Scalable check deposit (up to 30 checks in a single bunch)*
- Scalable deposit module - 1 slot for cash and check deposit. Can handle check and cash as a separate transaction but also mixed media (SW dependent). Up to 2,000 notes and 1,600 checks capacity*
- Envelope Depository with optional dispenser
- Coin Processing - Optional coin dispense

ENVIRONMENTAL

- Temperature:
 - Standard: 50°F to 104°F (+10°C to +40°C)
 - With severe environment fitted: 32°F to 104°F (0°C to +40°C)
- Humidity (interior): 20% to 80%
- Acoustics: Sound power 65db (A) idle, 68db (A) operating

OPERATING PLATFORM

- A range of Intel® Processors
- 2GB or 4GB RAM
- 500GB hard drive
- DVD-RW drive

SOFTWARE

- Windows® 7
- NCR APTRA XFS
- NCR APTRA software

ADDITIONAL FEATURES

- Biometrics ready
- Contactless ready

*Dependent upon currency, note quality and deposit module used

WHY NCR?

NCR Corporation (NYSE: NCR) is a leader in omni-channel solutions, turning everyday interactions with businesses into exceptional experiences. With its software, hardware, and portfolio of services, NCR enables nearly 700 million transactions daily across retail, financial, travel, hospitality, telecom and technology, and small business. NCR solutions run the everyday transactions that make your life easier.

NCR is headquartered in Duluth, Ga., with over 30,000 employees and does business in 180 countries. NCR is a trademark of NCR Corporation in the United States and other countries.

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR SelfServ, NCR Secure and APTRA are either registered trademarks or trademarks of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.

© 2017 NCR Corporation Patents Pending

17FIN8653-B-1217

ncr.com

